

Product information

18V Brushless Combi Drill LXT



DHP481RTJ

Chuck Capacity	1.5 - 13 mm
Blows per Minute (Hi) - ipm	0 - 31,500 ipm
Blows per Minute (Lo) - ipm	0 - 8,250 ipm
No Load Speed (Hi)	0 - 2100 rpm
No Load Speed (Lo)	0 - 550 rpm
Voltage	18 v
Max. in wood	76 mm
Max. in masonry	16 mm
Max. in steel	13 mm
Torque Settings	21 + drill
Battery Type	Lithium-ion
Vibration K factor	1.5 m/sec ²
Battery Quantity (5.0ah)	2
Max. Fastening Torque (Soft Joint)	60 Nm
Max. Fastening Torque (Hard Joint)	115 Nm
Vibration: Impact drilling into concrete	6.5 m/sec ²
Vibration: Drilling into metal	2.5 m/sec ²
Weight (with batteries)	2.7 - 3.0 kg



STANDARD EQUIPMENT: 197282-4 Battery BL1850B 18v Li-ion, 821550-0 MAKPAC CONNECTOR CASE (TYPE 2), 837916-4 MAKPAC INLAY FOT TYPE 2 CASE, DC18RC DC18RC COMPACT CHARGER

- Forward / reverse rotation
- Single sleeve keyless chuck allows for easy bit installation/removal by one hand.
- Electric brake
- Twin LED job light with afterglow.
- 2 mechanical gears.
- Battery fuel gauge
- Variable speed control by trigger
- Best possible ergonomic handle for drill-driver applications.
- Compact overall length.

Details correct as of: 15-1-2019

Makita reserve the right to change specifications at any time owing to their policy of constant improvement.

Accessories shown are not necessarily supplied.

www.makita.com